

Intec-G2® Series



POWER & CONTROL



EXPERIENCE & QUALITY



TECHNOLOGY & INNOVATION



A GMM Group Company



Techjet Upgrade Option - Linear Scale Feedback

ACCURACY WITH LINEAR SCALE FEEDBACK	0,05 mm/m - 0,002"
REPEATAB. WITH LINEAR SCALE FEEDBACK	± 0,025 mm - 0,001"

### TECHNICAL DATA

MODULE	i612-G2
MACHINE SIZE (L x W x H) Does not include pumps or control cabinet	4900 x 2650 x 2050 mm 193" x 104,3" x 80,7"
MACHINE WEIGHT	2300 kg - 5140 lb
MACHINE WEIGHT (with water)	8700 kg - 19180 lb
CUTTING TABLE DIMENSION	1860 x 3690 mm 73,2" x 145,3"
CUTTING AREA (without PAC60)	1830 x 3660 mm 72" x 144"
BEVEL CUTTING AREA (with PAC60)	not available
CUTTING AREA MAXIMIZED (with PAC60)	not available
ACCURACY OF MOTION	0,15 mm/m - 0,006"
REPEATABILITY OF MOTION	± 0,05 mm - 0,002"
MAX. AIR SPEED	17,5 m/min - 700 in/min
MAX. CUTTING SPEED	17,5 m/min - 700 in/min
MAX. MATERIAL THICKNESS (with PAC60)	200 mm - 8" (not available)

IMPORTANT NOTICE: the technical data is not binding and may be changed by Techni Waterjet without prior notice. All the above accuracy tolerances are correct at the calibration temperature of 20° ± 1° C.

Machines displayed in the present catalogue are without safety barriers in order to ensure the perfect vision of all the details of the machine.

# Intec-G2® 612

HIGH-PRESSURE WATERJET SYSTEMS


## STANDARD FEATURES

### REMOTE CONTROL PENDANT



The MPG allows to manually wind forward or backward through a cutting path. This enables the operator to find the exact point along a cutting path from which to re-start cutting after a stoppage, or to accurately locate a pre-cut part.


### BREAK AWAY HEAD



When the cutting head inadvertently crashes into a clamp or fixture, or hits the edge of a work piece or an upturned part, the Break Away Head will detect the crash and automatically stop the machine.

Not available with PAC60.

### TECH-SENSE




Tech-Sense Monitoring System provides the ability to run a night shift without the need for an attending operator. Should the cutting be disrupted, e.g. blocked nozzle, the machine will pause the program and send a text message to your cell phone.

### WATER RAISE AND LOWER



Automatic water Raise/Lower at the push of a button for Submerged Cutting; our tanks include air-tight welds of an air chamber which uses regular shop air pressure.

### SERVO Z AXIS



Programmable Z axis with auto height position recall, laser terrain mapping and edge location optics.

### HIGH-PRESSURE GAUGE



The HP gauge displays the pressure on the high-pressure water line. This allows the operator to see the actual pressure supplied to the cutting head and assists in troubleshooting.

## ELECTRIC SERVO PUMP - Patented

### Quantum NXT™

The Quantum NXT™ pump incorporates core "direct servo" technology that was first applied by NASA for the Space Shuttle Program.



MAX OUTPUT PRESSURE 3585 bar (52,000 psi)  
 MAX OUTPUT VOLUME 1.9 l/min (0.5 gpm)  
 Output Volume Based on 480 VAC Electrical Supply

### BENEFITS

- 60% more efficient than hydraulic intensifier
- Designed for quick seal service
- Virtually silent with noise level of 70 dbA



MAX OUTPUT PRESSURE 4550 bar (66,000 psi)  
 MAX OUTPUT VOLUME 3.8 l/min (1.0 gpm)  
 Output Volume Based on 480 VAC Electrical Supply